

# ME210 Triac amplifier



## **Summary**

ME220 is a triac module controlled by a 24 V AC signal. It amplifies the 24 V AC PWM output signal from an IRC controller or room unit (UI..., UX..., UC..., FC..., US...), which are able to control maximum 2 actuators per output only.

## **Application**

 Control of more radiators, fan coils, or any other heating or cooling circuits by a single controller.

#### **Function**

In a plastic casing suitable for monting into a flush box there is a board with terminals, triac and other components. When the input is energized the triac opens and gives 24 V AC control voltage for the actuators at the output terminals.

If more radiators or cooling panels are situated in a single space and controlled together, some of them may be hot while others stay cold. This is due to the characteristics of the actuator and valve set together with the hydraulic parameters of the installation, and it does not indicate wrong function of the controller or of the triac amplifier.

### **Technical data**

Control signal 24 V AC
Input current 20 mA
Working temperature 0...70 °C
Number of outputs (triacs) 1

Output load max. 2 A, e.g. 4 thermic actuators STA71

Terminals screw terminals, wire 0.14...1 mm<sup>2</sup>

Dimensions  $49 \times 49 \times 15 \text{ mm}$ 

domat ME210 1

### **Terminals**

## Inputs (screw terminals)

G power 24 V AC

G0 common ground

IN1 control input for triac (24 V AC)

## **Outputs (screw terminals)**

V1A output 24 V AC PWM

G0 common ground


V1B output 24 V AC PWM

G0 common ground

V1C output 24 V AC PWM

G0 common ground

### Connection



Do not overload the output – maximum triac load is 2 A. Note that the starting currents of cold thermic actuators may be higher than the nominal currents when the body is partially heated.

The output signal is brought to all terminals (V1A, V1B, V1C) for more comfortable installation.

08/2021 Subject to technical changes.

2 domat ME210