

## RFTF

## Room temperature and humidity sensor



**Summary**      The RFTF is a room temperature and relative humidity sensor for universal use in the HVAC sector.

**Application**      • HVAC systems – room temperature and humidity measuring

**Function**      The sensor measures temperature and relative humidity of air and other non-aggressive gases. It is used in refrigeration, air conditioning and clean room technology as well as in residential and public buildings. The temperature sensor has a range of 0 to +50 °C.

The sensors are intended for operating in a normal and chemically non-aggressive environment. They do not need any servicing or maintenance and can be mounted in any position. For humidity, capacitive sensing element is used.

The sensors are mounted with 2 or 4 screws on a flush-mounted junction box with 55 mm in diameter.

<b>Technical data</b>	Power supply	24 V AC +/- 20%, 15...36 V DC +/- 10% for U 15...36 V DC +/- 10% for I
	Output	0...10 V or 4...20 mA
	Operating range: temperature	0 ...+50 °C
	humidity	0...95% rH
	Protection type	IP30 (according to EN 60529)
	Protection class	III (according to EN 60730)
	Deviation	±3% rH (20...80% at 20°C), otherwise ±5% ±0,8 K at 20°C
	Terminals	screw terminals for wires 0,14 – 1,5 mm <sup>2</sup>
	Cover	ABS, RAL9010, optional stainless steel


Long-term stability	±1% per year
Dimensions	see below

### Sensor types

Type	Output rH	Output t
RFTF-I	4...20 mA	4...20 mA
RFTF-U	0...10 V	0...10 V
RFTF-U, Pt100	0...10 V	0...10 V + Pt100
RFTF-U, Pt1000	0...10 V	0...10 V + Pt1000
RFTF-U, Ni1000-6150	0...10 V	0...10 V + Ni1000-6150
RFTF-U, Ni1000-5000	0...10 V	0...10 V + Ni1000-5000
RFTF-U, NTC 1,8k	0...10 V	0...10 V + NTC 1.8k Ohm

### Terminals

#### RFTF-U



#### RFTF-U

- 1 +UB 24V AC/DC
- 2 Output humidity in % r.H. 0...10V
- 3 Output temperature in °C 0...10V
- 4 -UB-GND

#### RFTF-I

- 1 +UB 24 V DC
- 2 Output humidity in % r.H. 4...20 mA
- 3 Output temperature in °C 4...20 mA
- 4 -UB-GND (optional for backlighting)





**RFTF-U**  
**(passive temperature sensor)**

- 1 +UB 24V AC/DC
- 2 Output humidity in % r.H. 0...10V
- 3 Output temperature in °C 0...10V
- 4 -UB-GND
- 5 Passive element
- 6 e.g. Pt1000, Ni1000 ...

**RFTF-I**  
**(passive temperature sensor )**

- 1 +UB 24 V DC
- 2 Output humidity in % r.H. 4...20 mA
- 3 Output temperature in °C 4...20 mA
- 4 -UB-GND (optional for backlighting)
- 5 Passive element
- 6 e.g. Pt1000, Ni1000 ...

**Dimensions**



Dimensions are in *mm*.

**Changes in  
versions**

05/2016 — New housing design version.